



Outdoor luminaire for wall installation

Completely matt black inside to avoid any unwanted flare

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: 3 RGBW LEDs and a device to receive DMX standard 512 signal sent from the control unit 1181 or another compatible unit. The contained light source is intended for use in applications requiring high-quality coloured light

Rear cable entry

Color matching stainless steel Allen screws

Up to 32 luminaires can be connected to each control unit

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- Multi-channel setting

Dimensions	160 x 160 x 182 mm
Light source	LED RGBW
Multiple sources	2x
Light source info	max
Wattage	64 W
Power supply	220-240 V   50/60 Hz
Light source output	1980 lm
System output	1380 lm
System efficiency	23 lm/W
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	4.2 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**BI** WHITE

on request:


**CO** CORTEN  
**BR** BRONZE

### OPTIC

**standard** 30°  
 optional optics  
**10** 10°  
**54** 54°



ACCESSORIES



**RGBW** THE SERIES

