



Outdoor luminaire for wall/ceiling installation

Material: housing and base in low copper content die-cast aluminium / Aluminium internal plate

Diffuser: moulded opal glass / Silicone sealing gasket

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	Ø 260 x 171 mm
Light source	LED
Wattage	15 W
Power supply	220-240 V 50/60 Hz
Light source output	2300 lm
System output	645 lm
System efficiency	43 lm/W
Color Rendering Index – CRI	80
LED energy class	C
LED lifetime	L70 B50 72.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	2.6 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
BI	WHITE	4K	4000K

KASKO

THE SERIES

