



Outdoor luminaire for wall/ceiling installation

Material: housing and base in low copper content die-cast aluminium / Aluminium internal plate

Diffuser: moulded opal glass / Silicone sealing gasket

Light source: mains voltage LED module, compatible with phase-cut dimmers

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	267 x 165 x 125 mm
Light source	LED
Wattage	10 W
Power supply	220-240 V 50/60 Hz
Light source output	1125 lm
System output	470 lm
System efficiency	47 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	1.82 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
BI	WHITE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K



KASKO THE SERIES

