



Outdoor luminaire for wall/ceiling installation

Material: housing and base in low copper content die-cast aluminium / Aluminium internal plate

Diffuser: moulded opal glass / Silicone sealing gasket

Light source: mains voltage LED module, compatible with phase-cut dimmers

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	<b>267 x 165 x 125 mm</b>
Light source	<b>LED</b>
Wattage	<b>10 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>1125 lm</b>
System output	<b>470 lm</b>
System efficiency	<b>47 lm/W</b>
Color Rendering Index – CRI	<b>≥80</b>
LED energy class	<b>E (4000K), F (2700K), F (3000K)</b>
LED lifetime	<b>L70 B10 45.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>1.82 kg</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**

**FINISH**

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**BI** WHITE

**COLOUR TEMP.**

**27K** 2700K  
**3K** 3000K  
**4K** 4000K



**KASKO** THE SERIES

