



Outdoor luminaire for ceiling installation

Minimum thickness for surface installation / Recessed installation flush with the wall using backbox optional accessory

Material: low copper content die-cast aluminium

Ultra-white transparent tempered glass flush diffuser

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear cable entry

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**24V** 24V low voltage  
**HC** Honeycomb optic 10°

Dimensions	Ø 131 x H 41 mm
Light source	LED
Wattage	10 W
Power supply	220-240 V   50/60 Hz
Light source output	1125 lm
System output	750 lm
System efficiency	75 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	0.62 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

**AN** ANTHRACITE  
**BI** WHITE

on request:

**AG** ALUMINIUM GREY  
**CO** CORTEN  
**BR** BRONZE

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

### OPTIC

**standard** 40°

optional optics

**12** 12°  
**90** 90°



ACCESSORIES

