



Outdoor luminaire for wall/ceiling installation

Minimum thickness

Material: housing in low copper content die-cast aluminium / Internal wire holder plate in 99,8 aluminium

Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket

Built-in driver

Light source: LED unit

Suitable for through wiring installation by double cable entry

No visible frontal screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):


- S Version with sensor
- D Dimmable version

Dimensions	Ø 365 x 70 mm
Light source	LED
Wattage	29 W
Power supply	220-240 V   50/60 Hz
Light source output	4400 lm
System output	3250 lm
System efficiency	112 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	2.7 kg
Conformity	CE UK CA

## CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
BI	WHITE	4K	4000K

ACCESSORIES



LUNETTE

THE SERIES

