



Outdoor luminaire for wall/ceiling installation
 Minimum thickness
 Material: housing in low copper content die-cast aluminium / Internal wire holder plate in 99,8 aluminium
 Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket
 Driver + 3h emergency unit inside
 Light source: LED unit
 Suitable for through wiring installation by double cable entry
 No visible frontal screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):


- S Version with sensor
- D Dimmable version

Dimensions	Ø 365 x 70 mm
Light source	LED
Light source info	Emergenza 5W
Wattage	29 W
Power supply	220-240 V 50/60 Hz
Light source output	4400 lm
System output	3250 lm
System efficiency	112 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1 +2-22
Weight	3.1 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
BI	WHITE	4K	4000K

ACCESSORIES



LUNETTE THE SERIES

