



Outdoor luminaire for ceiling installation

Material: housing and glass holding frame in low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear cable entry

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
12-24V low voltage

Dimensions	110 x 110 x H 36 mm
Light source	LED
Wattage	15 W
Power supply	220-240 V 50/60 Hz
Light source output	1660 lm
System output	950 lm
System efficiency	63 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	1.1 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE
BI WHITE

on request:

CO CORTEN
BR BRONZE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 38°

optional optics

18 18°
90 90°

LUX SHOWER

THE SERIES

