



Outdoor luminaire for wall/ceiling installation  
 Material: polycarbonate ring and housing / Pre-wired 99,8 polished aluminium reflector  
 Diffuser: UV resistant opal polycarbonate  
 Luminaire supplied without light source  
 Rear or side cable entry by means of gland or conduit / Through wiring allowed  
 Stainless steel cross-head screws  
 Finish: UV resistant spray painting with polyurethane resins

|                             |                             |
|-----------------------------|-----------------------------|
| Dimensions                  | <b>200 x 110 x 110 mm</b>   |
| Light source                | <b>E27</b>                  |
| Light source info           | <b>L &lt; 166 mm</b>        |
| Wattage                     | <b>75 W</b>                 |
| Power supply                | <b>220-240 V   50/60 Hz</b> |
| Electrical insulation class | <b>Class I</b>              |
| IP rating                   | <b>IP 65</b>                |
| Impact resistance rating    | <b>IK 10 (20 joules)</b>    |
| Norms                       | <b>EN 60598-1 +2-1</b>      |
| Weight                      | <b>1.1 kg</b>               |
| Conformity                  | <b>CE UK<br/>CA</b>         |

**CODE OPTIONS**

**FINISH**

**AN** ANTHRACITE  
**BI** WHITE



**MARINA**

THE SERIES

