

Outdoor ground/wall recessed luminaire

Max. load pressure 2.000 kg (in-ground box + luminaire + covering flange together for drive-over use)

Material: low copper content die-cast aluminium

Diffuser: ultra-white opal tempered glass

Light source: mains voltage LED module, compatible with phase-cut dimmers / Fixed optic

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

24V 24V low voltage

Dimensions	Ø 107 x H 58 mm
Light source	LED
Wattage	8 W
Power supply	220-240 V 50/60 Hz
Light source output	835 lm
System output	347 lm
System efficiency	43 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F (3000K), F (4000K), G (2700K)
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-13
Weight	0.47 kg
Conformity	CE UK CA

CODE OPTIONS

COLOUR TEMP.


27K	2700K
3K	3000K
4K	4000K

PASSUM UP ULTRAFLAT Ø 125 aluminium LED 8W

1401


COMPONENTS

PASSUM UP ULTRAFLAT
Ø 125 IN-GROUND BOX



1423

PASSUM UP
Ø 125 ALUMINIUM ROUND
FLANGE



1521

PASSUM UP
Ø 125 STAINLESS STEEL
ROUND FLANGE



1522

PASSUM UP
Ø 125 STAINLESS STEEL
SQUARE FLANGE



1523