

Outdoor ground/wall recessed luminaire

Max. load pressure 2.000 kg (in-ground box + luminaire + covering flange together for drive-over use)

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit / Adjustable optics ±15°

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
10÷52V low voltage

Dimensions	Ø 107 x H 112 mm
Light source	LED
Wattage	8 W
Power supply	100-240 V   50/60 Hz
Light source output	951 lm
System output	636 lm
System efficiency	80 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-13
Weight	0.70 kg
Conformity	CE UK CA

### CODE OPTIONS

#### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K



#### OPTIC

**standard** 38°  
optional optics  
**18** 18°  
**90** 90°


**PASSUM UP Ø 125 aluminium LED 8W**

**1422**

COMPONENTS



ACCESSORIES



**PASSUM UP** THE SERIES

