

Outdoor ground/wall recessed luminaire

Max. load pressure 2.000 kg (in-ground box + luminaire + covering flange together for drive-over use)

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Driver not necessary

Luminaire supplied without light source / Adjustable optic $\pm 8^\circ$

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944)



Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

| | |
|------------------------------|-----------------------------|
| Dimensions | Ø 107 x H 112 mm |
| Light source | GU10 |
| Light source info | L < 57 mm |
| Wattage | 5 W |
| Power supply | 220-240 V 50/60 Hz |
| Electrical insulation class | Class I |
| IP rating | IP 65/67 |
| Impact resistance rating | IK 10 (20 joules) |
| Diffuser contact temperature | ≤ 40°C |
| Norms | EN 60598-1 +2-13 |
| Weight | 0.62 kg |
| Conformity | CE UK CA |


PASSUM UP Ø 125 aluminium GU10 5W

1424

COMPONENTS



ACCESSORIES



PASSUM UP THE SERIES

