

Outdoor ground/wall recessed luminaire

Max. load pressure 2.000 kg (in-ground box + luminaire + covering canopy together for drive-over use)

Material: low copper content die-cast aluminium

Diffuser: UV resistant polycarbonate

Built-in driver

Light source: LED unit / Adjustable optics 0+45°

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944)

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	Ø 180 x H 171 mm
Light source	LED
Wattage	8 W
Power supply	220-240 V   50/60 Hz
Light source output	850 lm
System output	605 lm
System efficiency	76 lm/W
Color Rendering Index – CRI	80
LED energy class	C (4000K), D (3000K)
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-13
Weight	2.2 kg
Conformity	CE UK CA


CODE OPTIONS

FINISH		COLOUR TEMP.		OPTIC	
AG	ALUMINIUM GREY	3K	3000K	standard	40°
AN	ANTHRACITE	4K	4000K	optional optics	
				12	12°


# PASSUM SPOT Ø 180 – ALUMINIUM LED 8W

## 1438

### COMPONENTS



### ACCESSORIES



### PASSUM SPOT THE SERIES

