
goccia ILLUMINAZIONE

PASSUM UP Ø 245 aluminium LED 29.5W

1442





Outdoor ground recessed luminaire

Max. load pressure 3.500 kg (in-ground box + luminaire + covering flange together for drive-over use)

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit / Adjustable optics ±25°

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	Ø 218 x H 266 mm
Light source	LED
Multiple sources	3x
Wattage	29.5 W
Power supply	220-240 V | 50/60 Hz
Light source output	4215 lm
System output	3180 lm
System efficiency	108 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-13
Weight	3.3 kg
Conformity	CE UKCA

CODE OPTIONS

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

OPTIC

standard	38°

optional optics

18	18°
90	90°

goccia ILLUMINAZIONE

Goccia Illuminazione srl
via E.Fermi 59/65 - 25020 Poncarale (BS) Italy
+39 030 2640761 - info@www.goccia.it

IMQ CERTIFIED QUALITY MANAGEMENT SYSTEM ISO 9001:2015

IQNET RECOGNIZED CERTIFICATION

PASSUM UP Ø 245 aluminium LED 29.5W

1442

COMPONENTS

PASSUM
Ø 245 IN-GROUND BOX



1441

PASSUM UP
Ø 245 ALUMINIUM ROUND FLANGE



1541

PASSUM UP
Ø 245 STAINLESS STEEL ROUND FLANGE



1542

ACCESSORIES

ACCESSORIES
WATERPROOF CONNECTOR



1941

ACCESSORIES
WATERPROOF CONNECTOR



1944

ACCESSORIES
WATERPROOF CONNECTOR



1942

PASSUM UP
Ø 245 ANTI-GLARE LOUVRE



1972

PASSUM UP THE SERIES







