



Outdoor ceiling recessed luminaire

Suitable to be installed on false ceilings / Fastening brackets for false ceiling with thickness from 5 to 50 mm / False ceiling hole Ø min. 115 mm - Ø max. 116 mm

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit / Adjustable optics ±15°

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944) / Safety cable supplied

Stainless steel screws

Aluminium closing flange supplied

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):

10÷52V low voltage

RGBW RGBW version

Dimensions	Ø 125 x H 109 x H2 >130 mm
Light Source	LED
Power	8 W
Voltage/Frequency	220-240 V 50/60 Hz
Light output source	951 lm
LUMEN OUTPUT	636 lm
System efficiency	80 lm/W
Color Rendering Index – CRI	80
LED energy class	E
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-2
Weight	0.8 kg
Certifications	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

on request:

IN STAINLESS STEEL

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 38°

optional optics

18 18°

90 90°



PASSUM DOWNLIGHT

THE SERIES

