



Outdoor ceiling recessed luminaire

Suitable to be installed on false ceilings / Fastening brackets for false ceiling with thickness from 5 to 50 mm / False ceiling hole Ø min. 115 mm - Ø max. 116 mm

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit / Adjustable optics ±15°

Pre-wired with 0,5 m H07RN-F buri cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944) / Safety cable supplied

Stainless steel screws

Aluminium closing flange supplied

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

10÷52V low voltage

RGBW RGBW version

Dimensions	Ø 125 x H 109 x H2 >130 mm
Light source	LED
Wattage	8 W
Power supply	220-240 V   50/60 Hz
Light source output	951 lm
System output	636 lm
System efficiency	80 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-2
Weight	0.8 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE

on request:

**IN** STAINLESS STEEL

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

### OPTIC

**standard** 38°

optional optics

**18** 18°

**90** 90°



PASSUM DOWNLIGHT

THE SERIES

