



Outdoor ceiling recessed luminaire

Suitable to be installed on false ceilings / Fastening brackets for false ceiling with thickness from 5 to 50 mm / False ceiling hole Ø min. 115 mm - Ø max. 116 mm

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Driver not necessary

Luminaire supplied without light source / Adjustable optic $\pm 8^\circ$

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944) / Safety cable supplied

Stainless steel screws

Aluminium closing flange supplied

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	Ø 125 x H 109 x H2 >130 mm
Light source	GU10
Light source info	L < 57 mm
Wattage	5 W
Power supply	220-240 V 50/60 Hz
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-2
Weight	0.7 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

on request:

IN STAINLESS STEEL



PASSUM DOWNLIGHT

THE SERIES

