



Outdoor ceiling recessed luminaire

Suitable to be installed on false ceilings / Fastening brackets for false ceiling with thickness from 5 to 50 mm / False ceiling hole Ø min. 225 mm - Ø max. 226 mm

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit / Adjustable optics ±25°

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944) / Safety cable supplied

Stainless steel screws

Aluminium closing flange supplied

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

RGBW RGBW version

Dimensions	Ø 245 x H 263 x H2 >300 mm
Light source	LED
Multiple sources	3x
Wattage	29.5 W
Power supply	220-240 V 50/60 Hz
Light source output	4215 lm
System output	3180 lm
System efficiency	108 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-2
Weight	3.7 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY

AN ANTHRACITE

on request:

COLOUR TEMP.

27K 2700K

3K 3000K

4K 4000K

OPTIC

standard 38°

optional optics

18 18°



IN STAINLESS STEEL

90

90°



PASSUM DOWNLIGHT

THE SERIES

