



Outdoor ceiling recessed luminaire

Suitable to be installed on false ceilings / Fastening brackets for false ceiling with thickness from 5 to 50 mm / False ceiling hole Ø min. 225 mm - Ø max. 226 mm

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Luminaire supplied without light source / Adjustable optic  $\pm 25^\circ$

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944) / Safety cable supplied

Stainless steel screws

Aluminium closing flange supplied

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	<b>Ø 245 x H 263 x H2 &gt;300 mm</b>
Light source	<b>E27</b>
Light source info	<b>L &lt; 195 mm</b>
Wattage	<b>30 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65/67</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-2</b>
Weight	<b>3.2 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE

on request:

**IN** STAINLESS STEEL



PASSUM DOWNLIGHT

THE SERIES

