



Outdoor ceiling recessed luminaire

Suitable to be installed on false ceilings / Fastening brackets for false ceiling with thickness from 5 to 50 mm / False ceiling hole Ø min. 115 mm - Ø max. 116 mm

Material: low copper content die-cast aluminium

Diffuser: ultra-white opal tempered glass

Light source: mains voltage LED module, compatible with phase-cut dimmers / Fixed optic

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944) / Safety cable supplied

Stainless steel screws

Aluminium closing flange supplied

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

24V 24V low voltage

Dimensions	Ø 125 x H 55 x H2 >85 mm
Light source	LED
Wattage	8 W
Power supply	220-240 V 50/60 Hz
Light source output	835 lm
System output	347 lm
System efficiency	43 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F (3000K), F (4000K), G (2700K)
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-2
Weight	0.6 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

on request:

IN STAINLESS STEEL

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K



PASSUM DOWNLIGHT

THE SERIES

