

Outdoor ground/wall recessed luminaire

Max. load pressure 2.000 kg (in-ground box + luminaire + aluminium covering canopy together for drive-over use) / Max. load pressure 500 kg (in-ground box + luminaire + stainless steel covering canopy together for walk-over use)

Material: AISI 316L stainless steel

Diffuser: UV resistant polycarbonate

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit / Side emitter optic to direct the light along the ground surface

Pre-wired with 0,2 m silicone cable and heat-shrinkable insulation connectors

On request versions (additional code):

MT7 7 m cable length

| | |
|--|---------------------------------|
| Dimensions | Ø 61 x H 67 mm |
| Light source | LED |
| Wattage | 1 W |
| Power supply | 24 Vdc |
| Light source output | 155 lm |
| System output | 33 lm |
| System efficiency | 33 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | C (4000K), D (2700K), D (3000K) |
| LED lifetime | L70 B50 > 50.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class III |
| IP rating | IP 65/67 |
| Impact resistance rating | IK 10 (20 joules) |
| Diffuser contact temperature | ≤ 40°C |
| Norms | EN 60598-1 +2-13 |
| Weight | 0.3 kg |
| Conformity | CE UK CA |

CODE OPTIONS









COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

PASSUM SIDEWARDS Ø 70 stainless steel LED 1W

1481

COMPONENTS

| | | | |
|---|--|--|---|
| <p>PASSUM Ø 70 IN-GROUND BOX</p>  <p>1411</p> | <p>PASSUM SIDEWARDS Ø 70 ALUMINIUM COVERING CANOPY 1X90°</p>  <p>1515</p> | <p>PASSUM SIDEWARDS Ø 70 ALUMINIUM COVERING CANOPY 180°</p>  <p>1516</p> | <p>PASSUM SIDEWARDS Ø 70 ALUMINIUM COVERING CANOPY 2X90°</p>  <p>1517</p> |
| <p>PASSUM SIDEWARDS Ø 70 ALUMINIUM COVERING CANOPY 360°</p>  <p>1519</p> | <p>PASSUM SIDEWARDS Ø 70 STAINLESS STEEL COVERING CANOPY 1X90°</p>  <p>1591</p> | <p>PASSUM SIDEWARDS Ø 70 STAINLESS STEEL COVERING CANOPY 2X90°</p>  <p>1593</p> | <p>PASSUM SIDEWARDS Ø 70 STAINLESS STEEL COVERING CANOPY 360°</p>  <p>1594</p> |

ACCESSORIES

| | | |
|---|---|---|
| <p>ACCESSORIES 24V DRIVER - 24W</p>  <p>1924</p> | <p>ACCESSORIES 24V DRIVER - 60W</p>  <p>1925</p> | <p>ACCESSORIES PWM DRIVER</p>  <p>1953</p> |
|---|---|---|

PASSUM SIDEWARDS THE SERIES

