

Outdoor ground recessed luminaire

Max. load pressure 3.500 kg (in-ground box + luminaire + covering flange together for drive-over use)

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: 3 RGBW LEDs and a device to receive DMX standard 512 signal sent from the control unit 1181 or another compatible unit. The contained light source is intended for use in applications requiring high-quality coloured light

Adjustable optics  $\pm 25^\circ$

Supplied with two 0,5 m cables: signal + 230V

Up to 32 luminaires can be connected to each control unit

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

Multi-channel setting

Dimensions	$\varnothing 218 \times H 266 \text{ mm}$
Light source	LED RGBW
Light source info	max
Wattage	32 W
Power supply	100-240 V   50/60 Hz
Light source output	990 lm
System output	690 lm
System efficiency	22 lm/W
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-13
Weight	3.3 kg
Conformity	CE UK CA

## CODE OPTIONS

### OPTIC

**standard** 30°

optional optics


**10** 10°

**54** 54°


# RGBW PASSUM UP 245 LED RGBW 32W

## 1482

### COMPONENTS



### ACCESSORIES



### RGBW THE SERIES

