

Outdoor ground/wall recessed luminaire

Max. load pressure 2.000 kg (in-ground box + luminaire + covering canopy together for drive-over use)

Material: AISI 316L stainless steel

Diffuser: UV resistant polycarbonate

Built-in driver

Light source: LED unit / Side emitter optic to direct the light along the ground surface

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944)

On request versions (additional code):

LV 10÷52V low voltage

Dimensions	Ø 107 x H 112 mm
Light source	LED
Wattage	4 W
Power supply	100-240 V 50/60 Hz
Light source output	470 lm
System output	68 lm
System efficiency	17 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Diffuser contact temperature	≤ 40°C
Norms	EN 60598-1 +2-13
Weight	0.7 kg
Conformity	CE UK CA

CODE OPTIONS

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

PASSUM SIDEWARDS Ø 125 stainless steel LED 4W

1485

COMPONENTS

PASSUM
Ø 125 IN-GROUND BOX



1421

PASSUM SIDEWARDS
Ø 125 ALUMINIUM COVERING
CANOPY 1X90°



1525

PASSUM SIDEWARDS
Ø 125 ALUMINIUM COVERING
CANOPY 180°



1526

PASSUM SIDEWARDS
Ø 125 ALUMINIUM COVERING
CANOPY 2X90°



1527


PASSUM SIDEWARDS
Ø 125 ALUMINIUM COVERING
CANOPY 360°



1529

ACCESSORIES

ACCESSORIES
WATERPROOF CONNECTOR



1941

ACCESSORIES
WATERPROOF CONNECTOR



1944

ACCESSORIES
WATERPROOF CONNECTOR



1942

PASSUM SIDEWARDS

THE SERIES

