

Outdoor ground/wall recessed luminaire
 Max. load pressure 2.000 kg (in-ground box + luminaire + covering canopy together for drive-over use)
 Material: AISI 316L stainless steel
 Diffuser: UV resistant polycarbonate
 Built-in driver
 Light source: LED unit / Adjustable optics 0+45°
 Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately - codes 1941-1942-1944)
 Stainless steel Allen screws

Dimensions	Ø 180 x H 171 mm
Light source	LED
Wattage	8 W
Power supply	220-240 V 50/60 Hz
Light source output	850 lm
System output	605 lm
System efficiency	76 lm/W
Color Rendering Index – CRI	80
LED energy class	C (4000K), D (3000K)
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-13
Weight	2.3 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

COLOUR TEMP.

3K 3000K
4K 4000K


OPTIC

standard 40°
 optional optics
12 12°


PASSUM SPOT Ø 180 – STAINLESS STEEL + ALUMINIUM COVER LED 8W

1488

COMPONENTS



ACCESSORIES



PASSUM SPOT THE SERIES

