

Outdoor ground/wall recessed luminaire

Max. load pressure 1.000 kg (in-ground box + luminaire + covering flange together for walk-over use)

Material: AISI 316L stainless steel

Diffuser: ultra-white transparent tempered glass

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit / Fixed optics

Pre-wired with 0,2 m silicone cable and heat-shrinkable insulation connectors

On request versions (additional code):
MT7 7 m cable length

Dimensions	Ø 61 x H 80 mm
Light source	LED
Wattage	1 W
Power supply	24 Vdc
Light source output	155 lm
System output	88 lm
System efficiency	88 lm/W
Color Rendering Index – CRI	80
LED energy class	C (4000K), D (2700K), D (3000K)
LED lifetime	L70 B50 > 60.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Diffuser contact temperature	≤ 40°C
Weight	0.17 kg
Conformity	CE UK CA

CODE OPTIONS

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K


OPTIC

standard 38°
 optional optics
18 18°
90 90°

PASSUM UP Ø 70 stainless steel LED 1W

1491

COMPONENTS



ACCESSORIES



PASSUM UP THE SERIES

