

Outdoor ground/wall recessed luminaire

Max. load pressure 1.000 kg (in-ground box + luminaire + covering flange together for walk-over use)

Material: AISI 316L stainless steel

Diffuser: ultra-white transparent tempered glass

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit / Fixed optics

Pre-wired with 0,2 m silicone cable and heat-shrinkable insulation connectors

On request versions (additional code):  
**MT7** 7 m cable length

Dimensions	Ø 61 x H 80 mm
Light source	LED
Wattage	3 W
Power supply	24 Vdc
Light source output	300 lm
System output	162 lm
System efficiency	54 lm/W
Color Rendering Index – CRI	80
LED energy class	C (4000K), D (2700K), D (3000K)
LED lifetime	L70 B50 > 60.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Diffuser contact temperature	≤ 40°C
Weight	0.17 kg
Conformity	CE UK CA

**CODE OPTIONS**

**COLOUR TEMP.**

**27K** 2700K  
**3K** 3000K  
**4K** 4000K


**OPTIC**

**standard** 38°  
 optional optics  
**18** 18°  
**90** 90°

**PASSUM UP Ø 70 stainless steel LED 3W**

**1494**

COMPONENTS



ACCESSORIES



**PASSUM UP** THE SERIES

