

Outdoor projector for wall, pole and ground installation

Adjustable hooking bracket

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass, sealed to the frame

Light source: mains voltage LED module, compatible with phase-cut dimmers / Round symmetric optics

Supplied with 1 m cable

Color matching side fixing screws in stainless steel

Optional surge protection device (SPD) to be ordered separately

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

MT4 4 m cable length for pole mounting

Dimensions	Ø 270 x 347 x 68 mm
Light source	LED
Wattage	20 W
Power supply	220-240 V 50/60 Hz
Light source output	2250 lm
System output	1500 lm
System efficiency	75 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-5
Weight	3.9 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 40°
optional optics
12 12°
90 90°

ACCESSORIES

ACCESSORIES
SPD



1965

ACCESSORIES
POLE H 2500 – BURIABLE




3504

ACCESSORIES
POLE H 3000 – BURIABLE




3505

PROTO
SINGLE POLE CONNECTION



5061

PROTO
DOUBLE POLE CONNECTION



5062

ACCESSORIES
POLE H 3500 – BURIABLE



3506

PROTO THE SERIES

