



Outdoor projector for wall, pole and ground installation  
 Adjustable hooking bracket  
 Material: low copper content die-cast aluminium  
 Diffuser: ultra-white transparent tempered glass, sealed to the frame  
 Light source: mains voltage LED module, compatible with phase-cut dimmers / Round symmetric optics  
 Supplied with 1 m cable  
 Color matching side fixing screws in stainless steel  
 Optional surge protection device (SPD) to be ordered separately  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
**MT4** 4 m cable length for pole mounting

Dimensions	Ø 270 x 347 x 68 mm
Light source	LED
Wattage	30 W
Power supply	220-240 V   50/60 Hz
Light source output	3320 lm
System output	2100 lm
System efficiency	70 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-5
Weight	3.9 kg
Conformity	CE UK CA

### CODE OPTIONS

#### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE

#### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

#### OPTIC

**standard** 40°  
 optional optics  
**12** 12°  
**90** 90°

ACCESSORIES

ACCESSORIES  
SPD



1965

ACCESSORIES  
POLE H 2500 – BURIABLE



3504

ACCESSORIES  
POLE H 3000 – BURIABLE



3505

PROTO  
SINGLE POLE CONNECTION



5061

PROTO  
DOUBLE POLE CONNECTION



5062

ACCESSORIES  
POLE H 3500 – BURIABLE



3506

**PROTO** THE SERIES

