

Outdoor projector for wall, pole and ground installation  
 Adjustable hooking bracket  
 Material: low copper content die-cast aluminium  
 Diffuser: ultra-white transparent tempered glass, sealed to the frame  
 Light source: mains voltage LED module, compatible with phase-cut dimmers / Round symmetric optics  
 Supplied with 1 m cable  
 Color matching side fixing screws in stainless steel  
 Optional surge protection device (SPD) to be ordered separately  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
**MT4** 4 m cable length for pole mounting

Dimensions	<b>Ø 270 x 347 x 68 mm</b>
Light source	<b>LED</b>
Wattage	<b>30 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>3320 lm</b>
System output	<b>2100 lm</b>
System efficiency	<b>70 lm/W</b>
Color Rendering Index – CRI	<b>≥80</b>
LED energy class	<b>E (4000K), F (2700K), F (3000K)</b>
LED lifetime	<b>L70 B10 45.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 66</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-5</b>
Weight	<b>3.9 kg</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**

**FINISH**

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE

**COLOUR TEMP.**

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

**OPTIC**

**standard** 40°  
 optional optics  
**12** 12°  
**90** 90°


ACCESSORIES

ACCESSORIES  
SPD



1965

ACCESSORIES  
POLE H 2500 – BURIABLE




3504

ACCESSORIES  
POLE H 3000 – BURIABLE




3505

PROTO  
SINGLE POLE CONNECTION




5061

PROTO  
DOUBLE POLE CONNECTION



5062

ACCESSORIES  
POLE H 3500 – BURIABLE



3506

**PROTO** THE SERIES

