



Outdoor projector for wall, pole and ground installation
 Adjustable hooking bracket
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white transparent tempered glass, sealed to the frame
 Built-in driver
 Light source: highly performing LED modules / Symmetric and asymmetric STRADA optics
 Supplied with 1 m cable
 Color matching side fixing screws in stainless steel
 Optional surge protection device (SPD) to be ordered separately
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- MT4 4 m cable length for pole mounting

Dimensions	Ø 270 x 347 x 68 mm
Light source	LED
Wattage	25 W
Power supply	220-240 V 50/60 Hz
Light source output	3008 lm
System output	2626 lm
System efficiency	105 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L90 B10 > 100.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-5
Weight	4 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 100°

optional optics

01 17°
02 150° X 45°
03 90° X 30°
04 120° X 45°
05 150° X 70°

ACCESSORIES

ACCESSORIES
SPD



1965

ACCESSORIES
POLE H 2500 – BURIABLE



3504

ACCESSORIES
POLE H 3000 – BURIABLE



3505

PROTO
SINGLE POLE CONNECTION



5061

PROTO
DOUBLE POLE CONNECTION



5062

ACCESSORIES
POLE H 3500 – BURIABLE



3506