

Outdoor projector for wall, pole and ground installation  
 Adjustable hooking bracket  
 Material: low copper content die-cast aluminium  
 Diffuser: ultra-white transparent tempered glass, sealed to the frame  
 Built-in driver  
 Light source: highly performing LED modules / Symmetric and asymmetric STRADA optics  
 Supplied with 1 m cable  
 Color matching side fixing screws in stainless steel  
 Optional surge protection device (SPD) to be ordered separately  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- MT4 4 m cable length for pole mounting

|  |                      |
|--|----------------------|
| Dimensions                               | Ø 270 x 347 x 68 mm  |
| Light source                             | LED                  |
| Wattage                                  | 25 W                 |
| Power supply                             | 220-240 V   50/60 Hz |
| Light source output                      | 3008 lm              |
| System output                            | 2626 lm              |
| System efficiency                        | 105 lm/W             |
| Color Rendering Index – CRI              | 80                   |
| LED energy class                         | D                    |
| LED lifetime                             | L90 B10 > 100.000 h  |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3       |
| Electrical insulation class              | Class I              |
| IP rating                                | IP 66                |
| Impact resistance rating                 | IK 08 (5 Joules)     |
| Norms                                    | EN 60598-1 +2-5      |
| Weight                                   | 4 kg                 |
| Conformity                               | CE UK CA             |

**CODE OPTIONS**

**FINISH**

- AG ALUMINIUM GREY
- AN ANTHRACITE

**COLOUR TEMP.**

- 27K 2700K
- 3K 3000K
- 4K 4000K

**OPTIC**

- standard 100°
- optional optics
- 01 17°
- 02 150° X 45°
- 03 90° X 30°
- 04 120° X 45°
- 05 150° X 70°


ACCESSORIES

**ACCESSORIES**  
SPD



**1965**

**ACCESSORIES**  
POLE H 2500 – BURIABLE




**3504**

**ACCESSORIES**  
POLE H 3000 – BURIABLE




**3505**

**PROTO**  
SINGLE POLE CONNECTION



**5061**

**PROTO**  
DOUBLE POLE CONNECTION



**5062**

**ACCESSORIES**  
POLE H 3500 – BURIABLE



**3506**