

Outdoor projector for wall, pole and ground installation  
 Adjustable hooking bracket  
 Material: low copper content die-cast aluminium  
 Diffuser: ultra-white transparent tempered glass, sealed to the frame  
 Built-in driver  
 Light source: highly performing LED modules / Symmetric and asymmetric STRADA optics  
 Supplied with 1 m cable  
 Color matching side fixing screws in stainless steel  
 Optional surge protection device (SPD) to be ordered separately  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- MT4 4 m cable length for pole mounting

Dimensions	<b>Ø 270 x 347 x 68 mm</b>
Light source	<b>LED</b>
Wattage	<b>35 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>4212 lm</b>
System output	<b>3352 lm</b>
System efficiency	<b>96 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>D</b>
LED lifetime	<b>L90 B10 &gt; 100.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 66</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-5</b>
Weight	<b>4 kg</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**

**FINISH**

- AG** ALUMINIUM GREY
- AN** ANTHRACITE

**COLOUR TEMP.**

- 27K** 2700K
- 3K** 3000K
- 4K** 4000K

**OPTIC**

- standard** 100°
- optional optics
- 01** 17°
- 02** 150° X 45°
- 03** 90° X 30°
- 04** 120° X 45°
- 05** 150° X 70°




ACCESSORIES

**ACCESSORIES**  
SPD



**1965**

**ACCESSORIES**  
POLE H 2500 – BURIABLE




**3504**

**ACCESSORIES**  
POLE H 3000 – BURIABLE




**3505**

**PROTO**  
SINGLE POLE CONNECTION



**5061**

**PROTO**  
DOUBLE POLE CONNECTION



**5062**

**ACCESSORIES**  
POLE H 3500 – BURIABLE



**3506**