

Outdoor projector for wall, pole and ground installation  
Adjustable hooking bracket  
Material: low copper content die-cast aluminium  
Diffuser: ultra-white transparent tempered glass, sealed to the frame  
Built-in driver  
Light source: highly performing LED modules / Symmetric and asymmetric STRADA optics  
Supplied with 1 m cable  
Color matching side fixing screws in stainless steel  
Optional surge protection device (SPD) to be ordered separately  
Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- MT4 4 m cable length for pole mounting

Dimensions	Ø 270 x 347 x 68 mm
Light source	LED
Wattage	35 W
Power supply	220-240 V   50/60 Hz
Light source output	4212 lm
System output	3352 lm
System efficiency	96 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L90 B10 > 100.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-5
Weight	4 kg
Conformity	CE UK CA

**CODE OPTIONS**

**FINISH**

- AG ALUMINIUM GREY
- AN ANTHRACITE

**COLOUR TEMP.**

- 27K 2700K
- 3K 3000K
- 4K 4000K

**OPTIC**

- standard 100°
- optional optics
- 01 17°
- 02 150° X 45°
- 03 90° X 30°
- 04 120° X 45°
- 05 150° X 70°


ACCESSORIES

ACCESSORIES  
SPD



1965

ACCESSORIES  
POLE H 2500 – BURIABLE




3504

ACCESSORIES  
POLE H 3000 – BURIABLE




3505

PROTO  
SINGLE POLE CONNECTION



5061

PROTO  
DOUBLE POLE CONNECTION



5062

ACCESSORIES  
POLE H 3500 – BURIABLE



3506