

**PROTO RGBW** LED RGBW 17.5W

**4939**



Outdoor projector for wall, pole and ground installation

Adjustable hooking bracket

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass, sealed to the frame

Built-in driver

Light source: 6 RGBW LEDs and a device to receive DMX standard 512 signal sent from the control unit 1181 or another compatible unit. The contained light source is intended for use in applications requiring high-quality coloured light

Supplied with 1 m cable: signal + 230V

Color matching side fixing screws in stainless steel

Up to 32 luminaires can be connected to each control unit

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):  
Multi-channel setting

Dimensions	Ø 270 x 347 x 68 mm
Light Source	LED RGBW
Power	17.5 W
Voltage/Frequency	220-240 V   50/60 Hz
Light output source	1750 lm
LUMEN OUTPUT	1150 lm
System efficiency	66 lm/W
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-5
Weight	4 kg
Certifications	CE UK CA


**CODE OPTIONS**

**FINISH**

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE

**OPTIC**





**standard** 30°  
optional optics  
**10** 10°  
**54** 54°



**PROTO RGBW** LED RGBW 17.5W

**4939**

ACCESSORIES

<div>ACCESSORIES</div> <div>BURIABLE POLE H 2500</div> <div></div> <div>3504</div>	<div>ACCESSORIES</div> <div>BURIABLE POLE H 3000</div> <div></div> <div>3505</div>	<div>PROTO STRADA</div> <div>SINGLE POLE CONNECTION</div> <div></div> <div>5061</div>	<div>PROTO STRADA</div> <div>DOUBLE POLE CONNECTION</div> <div></div> <div>5062</div>
---	---	--	--

**PROTO** THE SERIES

