

Outdoor wall recessed luminaire

Material: polycarbonate

Built-in driver

Light source: LED unit

Color matching stainless steel Allen screws

On request versions (additional code):

LV 10=52V low voltage

Dimensions	186 x 70 x 50 mm
Light source	LED
Wattage	4.5 W
Power supply	100-240 V   50/60 Hz
Light source output	480 lm
System output	325 lm
System efficiency	72 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-2
Weight	0.29 kg
Conformity	CE UK CA

## CODE OPTIONS

### COLOUR TEMP.


**3K** 3000K  
**4K** 4000K

**QUANTUM 6 MOD. HORIZONTAL FRONT** LED 4.5W

**5440**


COMPONENTS

**QUANTUM**  
6 MOD. POLYCARBONATE MASK




**5455**

**QUANTUM**  
6 MOD. ALUMINIUM MASK




**5465**

**QUANTUM**  
6 MOD. ALUMINIUM MASK




**5466**

**QUANTUM**  
6 MOD. ALUMINIUM MASK




**5467**

**QUANTUM**  
6 MOD. STAINLESS STEEL MASK



**5475**

**QUANTUM**  
6 MOD. STAINLESS STEEL MASK



**5476**

**QUANTUM**  
6 MOD. STAINLESS STEEL MASK



**5477**

**QUANTUM**  
6 MOD. BACKBOX



**5482**

**QUANTUM** THE SERIES

