

Outdoor wall recessed luminaire

Material: polycarbonate

Built-in driver

Light source: LED unit

Color matching stainless steel Allen screws

On request versions (additional code):

LV 10=52V low voltage

Dimensions	186 x 70 x 50 mm
Light source	LED
Wattage	4.5 W
Power supply	100-240 V   50/60 Hz
Light source output	480 lm
System output	325 lm
System efficiency	72 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-2
Weight	0.29 kg
Conformity	CE UK CA

#### CODE OPTIONS







#### COLOUR TEMP.

3K 3000K  
4K 4000K

# QUANTUM 6 MOD. HORIZONTAL FRONT LED 4.5W

## 5440

### COMPONENTS

<p><b>QUANTUM</b> 6 MOD. POLYCARBONATE MASK</p>  <p><b>5455</b></p>	<p><b>QUANTUM</b> 6 MOD. ALUMINIUM MASK</p>  <p><b>5465</b></p>	<p><b>QUANTUM</b> 6 MOD. ALUMINIUM MASK</p>  <p><b>5466</b></p>	<p><b>QUANTUM</b> 6 MOD. ALUMINIUM MASK</p>  <p><b>5467</b></p>
<p><b>QUANTUM</b> 6 MOD. STAINLESS STEEL MASK</p>  <p><b>5475</b></p>	<p><b>QUANTUM</b> 6 MOD. STAINLESS STEEL MASK</p>  <p><b>5476</b></p>	<p><b>QUANTUM</b> 6 MOD. STAINLESS STEEL MASK</p>  <p><b>5477</b></p>	<p><b>QUANTUM</b> 6 MOD. BACKBOX</p>  <p><b>5482</b></p>

### QUANTUM THE SERIES

