

Pole complete with luminaire and relative covering mask  
 Stainless steel plate holding the anchoring set incorporated  
 (stainless steel ground anchors code 5529 supplied separately)  
 Material: aluminium  
 Built-in driver  
 Light source: LED unit  
 Finish with double painting (epoxy-based primer and polyester  
 powder coating) after anti-corrosion treatments

On request versions (additional code):  
 D Dimmable version

Dimensions	194 x 104 x H 580 mm
Light source	LED
Wattage	13 W
Power supply	220-240 V   50/60 Hz
Light source output	1500 lm
System output	1123 lm
System efficiency	86 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	3.5 kg
Conformity	CE UK CA

## CODE OPTIONS


### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

ACCESSORIES



QUANTUM THE SERIES

