

Outdoor luminaire for wall/ceiling installation

Material: extruded aluminium housing / Die-cast aluminium frame
/ Polycarbonate side covers / 99,8 polished aluminium reflector

Diffuser: UV resistant opal polycarbonate

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- 24V 24V low voltage
- E Emergency

Dimensions	1007 x 116 x 116 mm
Light source	LED
Wattage	20 W
Power supply	220-240 V 50/60 Hz
System output	1192 lm
System efficiency	60 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	5.3 kg
Conformity	CE UK CA

CODE OPTIONS











FINISH

AG ALUMINIUM GREY
NE BLACK

COLOUR TEMP.

3K 3000K
4K 4000K

ACCESSORIES

<p>SUPERMAXI ADJUSTABLE ARMS</p>  <p>5080</p>	<p>SUPERMAXI SNAP BRACKET</p>  <p>5091</p>	<p>SUPERMAXI CABLE TRUNKING</p>  <p>5692</p>	<p>SUPERMAXI TRUNKING SIDE COVER</p>  <p>5693</p>
<p>SUPERMAXI TRUNKING FRONT COVER</p>  <p>5694</p>	<p>SUPERMAXI TRUNKING BRACKETS</p>  <p>5696</p>	<p>SUPERMAXI CORRIDOR MODULE - 1 PIR SENSOR</p>  <p>5700</p>	<p>SUPERMAXI CORRIDOR MODULE - 2 PIR SENSORS</p>  <p>5704</p>
<p>SUPERMAXI BLIND MODULE L 1348</p>  <p>5705</p>	<p>SUPERMAXI BLIND MODULE L 1578</p>  <p>5708</p>		

SMALL MIDI MAXI SUPERMAXI THE SERIES

