

Outdoor luminaire for wall/ceiling installation  
 Material: extruded aluminium housing / Die-cast aluminium frame  
 / Polycarbonate side covers / 99,8 polished aluminium reflector  
 Diffuser: UV resistant opal polycarbonate  
 Built-in driver  
 Light source: LED unit  
 Cable entry from either the rear or the side  
 Stainless steel Allen screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- 24V 24V low voltage
- E Emergency

Dimensions	<b>1348 x 116 x 116 mm</b>
Light source	<b>LED</b>
Wattage	<b>58 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
System output	<b>3432 lm</b>
System efficiency	<b>59 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>D</b>
LED lifetime	<b>L80 B20 &gt; 80.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class II</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>6.3 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS











### FINISH

**AG** ALUMINIUM GREY  
**NE** BLACK

### COLOUR TEMP.

**3K** 3000K  
**4K** 4000K

ACCESSORIES

<p>SUPERMAXI ADJUSTABLE ARMS</p>  <p>5080</p>	<p>SUPERMAXI SNAP BRACKET</p>  <p>5091</p>	<p>SUPERMAXI CABLE TRUNKING</p>  <p>5692</p>	<p>SUPERMAXI TRUNKING SIDE COVER</p>  <p>5693</p>
<p>SUPERMAXI TRUNKING FRONT COVER</p>  <p>5694</p>	<p>SUPERMAXI TRUNKING BRACKETS</p>  <p>5696</p>	<p>SUPERMAXI CORRIDOR MODULE - 1 PIR SENSOR</p>  <p>5700</p>	<p>SUPERMAXI CORRIDOR MODULE - 2 PIR SENSORS</p>  <p>5704</p>
<p>SUPERMAXI BLIND MODULE L 1348</p>  <p>5705</p>	<p>SUPERMAXI BLIND MODULE L 1578</p>  <p>5708</p>		

SMALL MIDI MAXI SUPERMAXI THE SERIES

