
SUPERMAXI L 1578 LED 34W

5232





Outdoor luminaire for wall/ceiling installation

Material: extruded aluminium housing / Die-cast aluminium frame / Polycarbonate side covers / 99,8 polished aluminium reflector

Diffuser: UV resistant opal polycarbonate

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D	Dimmable version
24V	24V low voltage
E	Emergency

Dimensions	1578 x 116 x 116 mm
Light source	LED
Wattage	34 W
Power supply	220-240 V | 50/60 Hz
System output	2039 lm
System efficiency	60 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	7.8 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
NE	BLACK

COLOUR TEMP.

3K	3000K
4K	4000K

SUPERMAXI L 1578 LED 34W

5232

ACCESSORIES

SUPERMAXI
ADJUSTABLE ARMS



5080

SUPERMAXI
SNAP BRACKET



5091

SUPERMAXI
CABLE TRUNKING



5692

SUPERMAXI
TRUNKING SIDE COVER



5693

SUPERMAXI
TRUNKING FRONT COVER



5694

SUPERMAXI
TRUNKING BRACKETS



5696

SUPERMAXI
CORRIDOR MODULE – 1 PIR SENSOR



5700

SUPERMAXI
CORRIDOR MODULE – 2 PIR SENSORS



5704

SUPERMAXI
BLIND MODULE L 1348



5705

SUPERMAXI
BLIND MODULE L 1578



5708

SMALL MIDI MAXI SUPERMAXI THE SERIES





