



Outdoor luminaire for wall/ceiling installation

Material: extruded aluminium housing / Die-cast aluminium frame / Polycarbonate side covers / 99,8 polished aluminium reflector

Diffuser: ultra-white opal tempered glass

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):
24V 24V low voltage

Dimensions	207 x 116 x 116 mm
Light Source	LED
Power	8.5 W
Voltage/Frequency	100-240 V 50/60 Hz
LUMEN OUTPUT	419 lm
System efficiency	49 lm/W
Color Rendering Index – CRI	80
LED energy class	D
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	1.4 kg
Certifications	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
NE BLACK

COLOUR TEMP.

3K 3000K
4K 4000K

OPTIC

standard DIFFUSE

ACCESSORIES



SMALL MIDI MAXI SUPERMAXI THE SERIES

