



Outdoor luminaire for wall/ceiling installation

Material: extruded aluminium housing / Die-cast aluminium frame / Polycarbonate side covers / 99,8 polished aluminium reflector

Diffuser: ultra-white opal tempered glass

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
24V 24V low voltage

Dimensions	<b>207 x 116 x 116 mm</b>
Light source	<b>LED</b>
Wattage	<b>8.5 W</b>
Power supply	<b>100-240 V   50/60 Hz</b>
System output	<b>419 lm</b>
System efficiency	<b>49 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>D</b>
LED lifetime	<b>L80 B20 &gt; 80.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class II</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>1.4 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH

**AG** ALUMINIUM GREY  
**NE** BLACK

### COLOUR TEMP.

**3K** 3000K  
**4K** 4000K

ACCESSORIES



SMALL MIDI MAXI SUPERMAXI THE SERIES

