



Outdoor luminaire for wall/ceiling installation

Material: extruded aluminium housing / Die-cast aluminium guard / Polycarbonate side covers / 99,8 polished aluminium reflector

Diffuser: ultra-white opal tempered glass

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting after anti-corrosion treatments:  
epoxy-based primer and polyester powder coating

On request versions (additional code):

24V 24V low voltage

#### Dimensions

207 x 116 x 116 mm

#### Light Source

LED

#### Power

8.5 W

#### Voltage/Frequency

100-240 V | 50/60 Hz

#### LUMEN OUTPUT

226 lm

#### System efficiency

27 lm/W

#### Color Rendering Index – CRI

80

#### LED energy class

D

#### Electrical insulation class

Class II

#### IP rating

IP 65

#### Impact resistance rating

IK 10 (20 joules)

#### Norms

EN 60598-1 +2-1

#### Weight

1.4 kg

#### Certifications

CE UKCA

#### CODE OPTIONS

##### FINISH

AG ALUMINIUM GREY  
NE BLACK

##### COLOUR TEMP.

3K 3000K  
4K 4000K

##### OPTIC

standard DIFFUSE

**SMALL L 207 with guard** LED 8.5W

**5609**



ACCESSORIES



**SMALL MIDI MAXI SUPERMAXI**

THE SERIES

