
SMALL L 207 with guard LED 8.5W

5609







Outdoor luminaire for wall/ceiling installation

Material: extruded aluminium housing / Die-cast aluminium guard / Polycarbonate side covers / 99,8 polished aluminium reflector

Diffuser: ultra-white opal tempered glass

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):

24V 24V low voltage

Dimensions	207 x 116 x 116 mm		
Light Source	LED		
Power	8.5 W		
Voltage/Frequency	100-240 V 50/60 Hz		
LUMEN OUTPUT	226 lm		
System efficiency	27 lm/W		
Color Rendering Index - CRI	80		
LED energy class	D		
Electrical insulation class	Class II		
IP rating	IP 65		
Impact resistance rating	IK 10 (20 joules)		
Norms	EN 60598-1 +2-1		
Weight	1.4 kg		
Certifications	C€ FR		

CODE OPTIONS

FINISH		COLO	COLOUR TEMP.		OPTIC	
AG	ALUMINIUM GREY	3K	3000K	standard	DIFFUSE	
NE	BLACK	ΔK	4000K			




SMALL L 207 with guard LED 8.5W

5609

ACCESSORIES





SMALL MIDI MAXI SUPERMAXI

THE SERIES







