



Outdoor luminaire for wall/ceiling installation

Material: extruded aluminium housing / Die-cast aluminium frame
/ Polycarbonate side covers / 99,8 polished aluminium reflector

Diffuser: ultra-white opal tempered glass

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- 24V 24V low voltage
- E Emergency
- PC Vandalproof polycarbonate diffuser

| | |
|--|------------------------------|
| Dimensions | 551 x 116 x 116 mm |
| Light source | LED |
| Wattage | 34 W |
| Power supply | 220-240 V 50/60 Hz |
| System output | 1677 lm |
| System efficiency | 49 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | D |
| LED lifetime | L80 B20 > 80.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class II |
| IP rating | IP 65 |
| Impact resistance rating | IK 08 (5 Joules) |
| Norms | EN 60598-1 +2-1 |
| Weight | 3.6 kg |
| Conformity | CE UK CA |

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
NE BLACK

COLOUR TEMP.

3K 3000K
4K 4000K

ACCESSORIES



SMALL MIDI MAXI SUPERMAXI THE SERIES

