



Outdoor luminaire for wall/ceiling installation

Material: extruded aluminium housing / Die-cast aluminium frame / Polycarbonate side covers / 99,8 polished aluminium reflector

Diffuser: ultra-white opal tempered glass

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version
24V 24V low voltage
E Emergency
PC Vandalproof polycarbonate diffuser

Dimensions	551 x 116 x 116 mm
Light source	LED
Wattage	34 W
Power supply	220-240 V 50/60 Hz
System output	1677 lm
System efficiency	49 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	3.6 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	3K	3000K
NE	BLACK	4K	4000K

ACCESSORIES



SMALL MIDI MAXI SUPERMAXI THE SERIES

