



Outdoor walk-over luminaire for ground surface installation  
 Max. load pressure 500 kg  
 Material: low copper content die-cast aluminium  
 Diffuser: UV resistant opal polycarbonate  
 External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately  
 PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately  
 Light source: LED unit / Side emitter optic to direct the light along the ground surface  
 Anticorodal anodized aluminium cable gland with watertight internal resin coating - AQUASTOP system / Luminaire supplied with 1,5 m polyurethane buriable cable 2x0,8  
 Stainless steel screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
**MT7** 7 m cable length

Dimensions	Ø 78 x H 27 mm
Light source	LED
Multiple sources	4x
Wattage	3 W
Power supply	24 Vdc
Light source output	300 lm
System output	178 lm
System efficiency	59 lm/W
Color Rendering Index – CRI	≥80
LED energy class	D
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class III
IP rating	IP 67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	0.23 kg
Conformity	CE UK CA

**CODE OPTIONS**

**FINISH**

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE

on request:

**CO** CORTEN  
**BR** BRONZE

**COLOUR TEMP.**

**27K** 2700K  
**3K** 3000K  
**4K** 4000K



ACCESSORIES

ACCESSORIES  
24V DRIVER – 24W



1924

ACCESSORIES  
24V DRIVER – 60W



1925

ACCESSORIES  
PWM DRIVER



1953