



Outdoor walk-over luminaire for ground surface installation
 Max. load pressure 500 kg
 Material: low copper content die-cast aluminium
 Diffuser: UV resistant opal polycarbonate
 External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately
 PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately
 Light source: LED unit
 Anticorrosional anodized aluminium cable gland with watertight internal resin coating - AQUASTOP system / Luminaire supplied with 1,5 m polyurethane buriable cable 2x0,8
 Stainless steel screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
MT7 7 m cable length

Dimensions	Ø 180 x H 43 mm
Light source	LED
Wattage	6.4 W
Power supply	24 Vdc
Light source output	640 lm
System output	130 lm
System efficiency	20 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
Electrical insulation class	Class III
IP rating	IP 67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	1.10 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	3K	3000K
AN	ANTHRACITE	4K	4000K

on request:

CO	CORTEN
BR	BRONZE

ACCESSORIES



SQUEEZE THE SERIES

