



Outdoor walk-over luminaire for ground surface installation  
 Max. load pressure 500 kg  
 Material: low copper content die-cast aluminium  
 Diffuser: UV resistant opal polycarbonate  
 External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately  
 PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately  
 Light source: LED unit  
 Anticorrosive anodized aluminium cable gland with watertight internal resin coating - AQUASTOP system / Luminaire supplied with 1,5 m polyurethane buriable cable 2x0,8  
 Stainless steel screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
**MT7** 7 m cable length

Dimensions	Ø 180 x H 43 mm
Light source	LED
Multiple sources	4x
Wattage	12.8 W
Power supply	24 Vdc
Light source output	1280 lm
System output	215 lm
System efficiency	17 lm/W
Color Rendering Index – CRI	≥80
LED energy class	G
Electrical insulation class	Class III
IP rating	IP 67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	0.90 kg
Conformity	CE UK CA

**CODE OPTIONS**

<b>FINISH</b>		<b>COLOUR TEMP.</b>	
<b>AG</b>	ALUMINIUM GREY	<b>3K</b>	3000K
<b>AN</b>	ANTHRACITE	<b>4K</b>	4000K

on request:

<b>CO</b>	CORTEN
<b>BR</b>	BRONZE

ACCESSORIES



**SQUEEZE** THE SERIES

