



Outdoor walk-over luminaire for ground surface installation  
 Max. load pressure 500 kg  
 Material: low copper content die-cast aluminium  
 Diffuser: UV resistant opal polycarbonate  
 Light source: mains voltage LED module, compatible with phase-cut dimmers  
 Anticorrosional anodized aluminium cable gland with watertight internal resin coating - AQUASTOP system / Luminaire supplied with 1,5 m polyurethane buriabile cable 3x1 H07RN-F  
 Stainless steel screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
**MT7** 7 m cable length

Dimensions	Ø 180 x H 43 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V   50/60 Hz
Light source output	368 lm
System output	94 lm
System efficiency	24 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	1.18 kg
Conformity	CE UK CA

**CODE OPTIONS**

FINISH		COLOUR TEMP.	
<b>AG</b>	ALUMINIUM GREY	<b>27K</b>	2700K
<b>AN</b>	ANTHRACITE	<b>3K</b>	3000K
		<b>4K</b>	4000K
on request:			
<b>CO</b>	CORTEN		
<b>BR</b>	BRONZE		

**SQUEEZE**

THE SERIES

